


- NOTE:-
- ~~1] SHUNTS ITEM FITTED TO LINKS IN POSITIONS SHOWN THIS IS~~
  - 2] ALL CONNECTORS [SK, PL, LK, IC SOCKETS] TO BE MOUNTED FLUSH AND PERPENDICULAR TO THE P.C.B.
  - 3] UNLESS OTHERWISE SHOWN, ALL RADIAL LEADED COMPONENTS TO BE MOUNTED PERPENDICULAR TO THE P.C.B. TO WITHIN  $\pm 15^\circ$ .
  - ~~4] ENSURE REAR PANEL ITEM IS AT  $90^\circ$  TO THE P.C.B. AFTER ASSEMBLY.~~
  - ~~5] USE WIRE ITEM XX TO HOLD DOWN CRYSTALS DO NOT SOLDER WIRE TO CAN.~~
  - 6] MAXIMUM PERMITTED BOW ACROSS THE EDGE CONNECTOR, TO BE  $\pm 0.25$ MM AFTER FLOW SOLDER.

2	10/05/94	ECO 3486	BGH	
1	08/12/93	AMR 3801	BGH	
ISS	DATE	DESC OF CHANGE	DRN	CHKD

SCALE	1:1	ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED		COPYRIGHT OF THIS DRAWING IS RESERVED BY ACORN COMPUTERS LTD. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY, EITHER WHOLLY OR IN PART, WITHOUT THE CONSENT OF ACORN COMPUTERS LTD.		© COPYRIGHT 1994 ACORN COMPUTERS LTD ACORN HOUSE VISION PARK HISTON CAMBRIDGE CB4 4AE ENGLAND	TITLE		
MATERIAL	SEE PARTSLIST						4 WAY BACKPLANE ASSEMBLY		
FINISH	SEE PARTSLIST								
WHOLE No.TOL	± 1MM	DECIMAL No.TOL	ANGLE TOL.				ACORN COMPUTERS LTD		A2